

MODEL **KW-50 Series**
1/4" Hex Impact Driver



KW-50 For Hard Joint



KW-50H For Soft Joint



KW-50S For Super Soft Joint

APPLICATIONS :

- Fastening work of small dia. bolts, nuts, screw, tapping screw below 5 mm.
- Screw setting work for motorbike and light vehicle.
- Assembly / disassembly work of small engines.
- Disassembly / fixing work of fender, bumper, and interior .
- Super light and compact.
- Very low noise and low vibration.

SPECIFICATIONS : (Performance figures are at 0.62 MPa(Pe) / 90 P.S.I. air pressure.)

Drive Size (KW-50)	1/4" Hex	
Capacity of Bolt Size	5 mm	... 3/16 in
Free Speed	10,500 r.p.m.	
Impact Per Min.	3,000 i.p.m.	
Weight (w/o socket)	0.8 kg	... 1.76 lbs
Length (w/o socket)	184 mm	... 7-1/4 in
Air Consumption	0.20 m ³ /min	... 7.1 c.f.m.
Hose Size	6.3 mm	... 1/4 in
Air Pressure	0.62 MPa	... 90 P.S.I.

** choice of 9 mm bit or 13 mm bit



KUKEN CO., LTD.

3-6-15 Nonoue, Habikino-shi, Osaka 583-0871, Japan
 Tel : +81-72-953-3346 Fax : +81-72-953-0605
 Web : www.kuken.co.jp/english E-mail : export1@kuken.co.jp



CAT. No. 240105-50