

Horizontal Pallet Strapping Machine

■ Easy Height Adjustment

Strapping height is quickly adjusted using the easily operated counterbalance that moves smoothly and effortlessly to the desired strap location.

■ Simple Operation

The innovative pendant switch allows operation of the machine from either side of the load while enabling the operator to control the feeding, tensioning, and sealing of the strap with one hand.

Operator control makes positioning of the strap and/or the placement of corner protection an easy task.

■ Versatile Tension Capability

Manual Tension or Automatic Tension are available by means of a simple selector switch.

< Manual Tension Mode >

The strap tension can be controlled manually via the Operation Arm, allowing edge protection to be secured to the pallet prior to strap completion.

< Auto Tension Mode >

Strap tension is applied automatically at a preselected level.



Battery operated version is also available.

D-53HE2

Standard Specifications

Dimension	Width	1230 mm
	Height	2830 mm
	Depth	700 mm
	Weight	160 kg
Package Height		170-2210 mm
Joint / Strap/ Coil		heat seal / polypropylene ID 200 X W 200 mm
Strap Width / Thickness		12 (15.5) mm
Strap Tension		Max. 690N (70 kgf)
Power Supply		110, 120, 220, 230, 240V Single Phase 50/60Hz 0.4kVA

Dimensions and specifications are subject to change without notice.
Modification rights reserved.

© 2020 Strapack Corporation

DISTRIBUTED BY:



ISO 9001 and 14001 Certified

STRAPACK CORPORATION
8-16-6 Ginza, Chuo-ku, Tokyo, 104-0061, JAPAN
Phone: 81-3-6278-1806 Fax: 81-3-6278-1807
(URL) <http://www.strapack.com> (E-mail) info@strapack.com
STRAPACK INC.
33508 Central Avenue, Union City, CA 94587-2097 U.S.A.
Phone :1-510-475-6000 Fax: 1-510-475-6090
STRAPACK, N.V./S.A.
Uilenbaan 200, B-2160 Wommelgem, BELGIUM
Phone: 32-3-355-1520 Fax: 32-3-355-1521